## NSN 5910-00-987-5456

Glass Dielectric Variable Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-987-5456
Thread Class:
2a
Body Style:
Piston
Bushing Diameter:
0.164 inches
Bushing Length:
0.406 inches
Body Length:
0.719 inches
Overall Diameter:
0.250 inches
Tempurature Coefficient Of Capacitance In Ppm Per Deg Celsius:
50.0 single section
<b>Tolerance Of Tempurature Coefficient In Ppm Per Deg Celsius:</b>
-50.0/+50.0 single section
Mounting Facility Screw Thread Series Designator:
Unc
Inclosure Type:
Encased
Adjustment Device Torque:
Between 2.000 inch-ounces and 6.000 inch-ounces
Bushing Shape:
Round
Mounting Facility Type And Quantity:
1 threaded bushing
Thready Qty Per Inch (tpi):
32
Nonderated Operating Temp:
Between -55.0 degrees celsius and 125.0 degrees celsius
Thread Size:
0.164 inches
Capacitance Range In Picofarads:
+0.4/+2.5 single section
Nonderated Voltage Rating And Type:
500.0 dc continuous single section
Adjustment Device Drive Type And Quantity:
1 slotted screw
Terminal Type And Quantity:
1 tab, solder lug
Shelf Life:

N/a

## NSN 5910-00-987-5456

Glass Dielectric Variable Capacitor - Page 2 of 2



			ure:	

--

Demilitarization:

No

Fiig:

A096a0