## NSN 5910-00-988-2744

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-988-2744 **Body Style:** W/thd bushing mtg, terminal (s) on one end Reliability Indicator: Not established **Terminal Length:** 0.296 inches **Body Diameter:** 1.000 inches **Body Length:** 2.312 inches **Schematic Diagram Designator:** Electrod (s) grounded to case **Mounting Facility Screw Thread Series Designator:** Unef **Mounting Facility Type And Quantity:** 1 threaded bushing **Insulation Resistance At Maximum Operating Temp:** 10.0 megohm-microfarads **Capacitance Value Per Section:** 10.000 microfarads single section **Nonderated Operating Temp:** Between -55.0 degrees celsius and 125.0 degrees celsius **Thread Size:** 0.312 inches Nonderated Continuous Voltage Rating And Type Per Section: 200.0 dc single section **Tolerance Range Per Section:** -10.00/+10.00 percent single section **Case Material:** Metal **Insulation Resistance At Reference Temp:** 2000.0 megohm-microfarads **Power Factor At Reference Tempurature In Percent:** 1.0000

**Terminal Surface Treatment:** 

Solder

**Terminal Type And Quantity:** 

1 tab, solder lug

Shelf Life:

N/a

**Unit Of Measure:** 

## NSN 5910-00-988-2744

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 2 of 2



_		••	• -				
1	em		ゖっ	riz	<b>2</b> †1	n	
_			ıιa	114	au	VII	١.

No

Fiig:

A010b0