NSN 5910-00-988-6164

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5910-00-988-6164

Body Style:
W/o mtg facilities, terminals on opposite surfaces
Reliability Indicator:
Not established
Terminal Length:
1.500 inches
Body Length:
1.000 inches
Body Width:
0.240 inches
Body Height:
0.410 inches
Terminal Diameter:
0.032 inches
Schematic Diagram Designator:
No common or grounded electrode (s)
Capacitance Value Per Section:
31910.000 picofarads single section
Nonderated Operating Temp:
Between -55.0 degrees celsius and 85.0 degrees celsius
No. 1 and 10 and a second seco
Nonderated Continuous Voltage Rating And Type Per Section:
200.0 dc single section
200.0 dc single section
200.0 dc single section Tolerance Range Per Section:
200.0 dc single section Tolerance Range Per Section: -2.00/+2.00 percent single section
200.0 dc single section Tolerance Range Per Section: -2.00/+2.00 percent single section Case Material:
200.0 dc single section Tolerance Range Per Section: -2.00/+2.00 percent single section Case Material: Plastic
200.0 dc single section Tolerance Range Per Section: -2.00/+2.00 percent single section Case Material: Plastic Insulation Resistance At Reference Temp:
200.0 dc single section Tolerance Range Per Section: -2.00/+2.00 percent single section Case Material: Plastic Insulation Resistance At Reference Temp: 10000.0 megohms
200.0 dc single section Tolerance Range Per Section: -2.00/+2.00 percent single section Case Material: Plastic Insulation Resistance At Reference Temp: 10000.0 megohms Terminal Surface Treatment:
200.0 dc single section Tolerance Range Per Section: -2.00/+2.00 percent single section Case Material: Plastic Insulation Resistance At Reference Temp: 10000.0 megohms Terminal Surface Treatment: Solder
200.0 dc single section Tolerance Range Per Section: -2.00/+2.00 percent single section Case Material: Plastic Insulation Resistance At Reference Temp: 10000.0 megohms Terminal Surface Treatment: Solder Terminal Type And Quantity:
200.0 dc single section Tolerance Range Per Section: -2.00/+2.00 percent single section Case Material: Plastic Insulation Resistance At Reference Temp: 10000.0 megohms Terminal Surface Treatment: Solder Terminal Type And Quantity: 2 uninsulated wire lead
200.0 dc single section Tolerance Range Per Section: -2.00/+2.00 percent single section Case Material: Plastic Insulation Resistance At Reference Temp: 10000.0 megohms Terminal Surface Treatment: Solder Terminal Type And Quantity: 2 uninsulated wire lead Shelf Life:
200.0 dc single section Tolerance Range Per Section: -2.00/+2.00 percent single section Case Material: Plastic Insulation Resistance At Reference Temp: 10000.0 megohms Terminal Surface Treatment: Solder Terminal Type And Quantity: 2 uninsulated wire lead Shelf Life: N/a
200.0 dc single section Tolerance Range Per Section: -2.00/+2.00 percent single section Case Material: Plastic Insulation Resistance At Reference Temp: 10000.0 megohms Terminal Surface Treatment: Solder Terminal Type And Quantity: 2 uninsulated wire lead Shelf Life: N/a
200.0 dc single section Tolerance Range Per Section: -2.00/+2.00 percent single section Case Material: Plastic Insulation Resistance At Reference Temp: 10000.0 megohms Terminal Surface Treatment: Solder Terminal Type And Quantity: 2 uninsulated wire lead Shelf Life: N/a Unit Of Measure:
200.0 dc single section Tolerance Range Per Section: -2.00/+2.00 percent single section Case Material: Plastic Insulation Resistance At Reference Temp: 10000.0 megohms Terminal Surface Treatment: Solder Terminal Type And Quantity: 2 uninsulated wire lead Shelf Life: N/a Unit Of Measure: Demilitarization: