NSN 5910-00-989-1955

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 1 of 2



| View Online at https://aerobasegroup.com/nsn/5910-00-989-1955 |
|---|
| Body Style: |
| W/o mtg facilities, axial terminals |
| Reliability Indicator: |
| Not established |
| Terminal Length: |
| 1.453 inches |
| Body Diameter: |
| 0.448 inches |
| Body Length: |
| 1.030 inches |
| Terminal Diameter: |
| 0.032 inches |
| Schematic Diagram Designator: |
| No common or grounded electrode (s) |
| Features Provided: |
| Hermetically sealed case |
| Insulation Resistance At Maximum Operating Temp: |
| 10.0 megohm-microfarads |
| Capacitance Value Per Section: |
| 0.180 microfarads single section |
| Nonderated Operating Temp: |
| Between -55.0 degrees celsius and 125.0 degrees celsius |
| Nonderated Continuous Voltage Rating And Type Per Section: |
| 200.0 dc single section |
| Tolerance Range Per Section: |
| -10.00/+10.00 percent single section |
| Case Material: |
| Metal |
| Insulation Resistance At Reference Temp: |
| 2000.0 megohm-microfarads |
| Dissipation Factor At Reference Tempurature In Percent: |
| 1.5000 |
| Power Factor At Reference Tempurature In Percent: |
| 1.0000 |
| Terminal Surface Treatment: |
| Solder |
| Case Insulation Material: |
| Plastic |
| Terminal Type And Quantity: |
| 2 uninsulated wire lead |
| Shelf Life: |

N/a

NSN 5910-00-989-1955

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 2 of 2



| | | • • | | | | | |
|---|----|-----|------|----|----|-----|-----|
| ш | ın | ıtı | r 1t | NЛ | മാ | CII | re: |
| | | | | | | | |

--

Demilitarization:

No

Fiig:

A010b0