

View Online at <https://aerobasegroup.com/nsn/5910-00-990-5467>

Body Style:

W/thd bushing mtg, terminals on opposite ends

Reliability Indicator:

Not established

Body Diameter:

0.312 inches

Body Length:

0.689 inches

Schematic Diagram Designator:

Feedthrough

Anode Type:

Solid

Electrical Polarization:

Polarized

Mounting Facility Screw Thread Series Designator:

Unc

Mounting Facility Type And Quantity:

1 threaded bushing

Features Provided:

Hermetically sealed case

Capacitance Value Per Section:

6.800 microfarads single section

Nonderated Operating Temp:

Between -80.0 degrees celsius and 85.0 degrees celsius

Thread Size:

0.250 inches

Nonderated Continuous Voltage Rating And Type Per Section:

35.0 dc single section

Tolerance Range Per Section:

-20.00/+20.00 percent single section

Case Material:

Metal

Capacitive Electrode Material:

Tantalum

Test Data Document:

89661-128c195h10 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Terminal Type And Quantity:

2 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A010b0