Plastic Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-990-6771

### **Body Style:**

W/o mtg facilities terminal (s) on one surface

- **Reliability Indicator:**
- Not established
- **Terminal Length:**
- 1.000 inches
- Body Length:
- 0.406 inches
- **Body Width:**
- 0.281 inches
- **Body Height:**

0.187 inches

### Center To Center Distance Between Terminals Parallel To Length:

Between 0.219 inches and 0.406 inches

#### **Schematic Diagram Designator:**

No common or grounded electrode (s)

# Internal Electrical Connection Type:

Extended foil

### Insulation Resistance At Maximum Operating Temp:

20.0 megohm-microfarads

## Capacitance Value Per Section:

22000.000 picofarads single section

### Nonderated Operating Temp:

Between -55.0 degrees celsius and 85.0 degrees celsius

### Nonderated Continuous Voltage Rating And Type Per Section:

50.0 dc single section

### **Tolerance Range Per Section:**

-10.00/+10.00 percent single section

### **Case Material:**

Plastic

### Insulation Resistance At Reference Temp:

50000.0 megohm-microfarads

### **Dissipation Factor At Reference Tempurature In Percent:**

1.0000

#### **Dielectric Material:**

Plastic polyethylene terephthalate

## **Terminal Type And Quantity:**

2 uninsulated wire lead

Shelf Life:

N/a

#### Unit Of Measure:

---



Demilitarization:

No

Fiig:

A010b0