NSN 5910-00-993-2754

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5910-00-993-2754

Body Style:
W/o mtg facilities, terminals on opposite surfaces
Reliability Indicator:
Not established
Terminal Length:
Between 1.500 inches and 1.501 inches
Body Length:
1.680 inches
Body Width:
0.560 inches
Body Height:
0.340 inches
Terminal Diameter:
0.020 inches
Schematic Diagram Designator:
No common or grounded electrode (s)
Capacitance Value Per Section:
5.000 microfarads single section
No. 1 and 10 and Tour
Nonderated Operating Temp:
Between -55.0 degrees celsius and 125.0 degrees celsius
Between -55.0 degrees celsius and 125.0 degrees celsius
Between -55.0 degrees celsius and 125.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section:
Between -55.0 degrees celsius and 125.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 100.0 dc single section
Between -55.0 degrees celsius and 125.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 100.0 dc single section Tolerance Range Per Section:
Between -55.0 degrees celsius and 125.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 100.0 dc single section Tolerance Range Per Section: -10.00/+10.00 percent single section
Between -55.0 degrees celsius and 125.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 100.0 dc single section Tolerance Range Per Section: -10.00/+10.00 percent single section Case Material:
Between -55.0 degrees celsius and 125.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 100.0 dc single section Tolerance Range Per Section: -10.00/+10.00 percent single section Case Material: Plastic
Between -55.0 degrees celsius and 125.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 100.0 dc single section Tolerance Range Per Section: -10.00/+10.00 percent single section Case Material: Plastic Terminal Type And Quantity:
Between -55.0 degrees celsius and 125.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 100.0 dc single section Tolerance Range Per Section: -10.00/+10.00 percent single section Case Material: Plastic Terminal Type And Quantity: 2 uninsulated wire lead
Between -55.0 degrees celsius and 125.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 100.0 dc single section Tolerance Range Per Section: -10.00/+10.00 percent single section Case Material: Plastic Terminal Type And Quantity: 2 uninsulated wire lead Shelf Life:
Between -55.0 degrees celsius and 125.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 100.0 dc single section Tolerance Range Per Section: -10.00/+10.00 percent single section Case Material: Plastic Terminal Type And Quantity: 2 uninsulated wire lead Shelf Life: N/a
Between -55.0 degrees celsius and 125.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 100.0 dc single section Tolerance Range Per Section: -10.00/+10.00 percent single section Case Material: Plastic Terminal Type And Quantity: 2 uninsulated wire lead Shelf Life: N/a
Between -55.0 degrees celsius and 125.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 100.0 dc single section Tolerance Range Per Section: -10.00/+10.00 percent single section Case Material: Plastic Terminal Type And Quantity: 2 uninsulated wire lead Shelf Life: N/a Unit Of Measure:
Between -55.0 degrees celsius and 125.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 100.0 dc single section Tolerance Range Per Section: -10.00/+10.00 percent single section Case Material: Plastic Terminal Type And Quantity: 2 uninsulated wire lead Shelf Life: N/a Unit Of Measure: Demilitarization:
Between -55.0 degrees celsius and 125.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 100.0 dc single section Tolerance Range Per Section: -10.00/+10.00 percent single section Case Material: Plastic Terminal Type And Quantity: 2 uninsulated wire lead Shelf Life: N/a Unit Of Measure: Demilitarization: No