## NSN 5910-00-994-0330

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5910-00-994-0330

Body Style:
W/o mtg facilities, terminals on opposite surfaces
Reliability Indicator:
Not established
Terminal Length:
1.625 inches
Body Length:
1.375 inches
Body Width:
0.437 inches
Body Height:
0.667 inches
Terminal Diameter:
0.032 inches
Schematic Diagram Designator:
No common or grounded electrode (s)
Capacitance Value Per Section:
5.000 microfarads single section
Nonderstad Operating Temps
Nonderated Operating Temp:
Between -55.0 degrees celsius and 85.0 degrees celsius
Between -55.0 degrees celsius and 85.0 degrees celsius
Between -55.0 degrees celsius and 85.0 degrees celsius  Nonderated Continuous Voltage Rating And Type Per Section:
Between -55.0 degrees celsius and 85.0 degrees celsius  Nonderated Continuous Voltage Rating And Type Per Section:  60.0 dc single section
Between -55.0 degrees celsius and 85.0 degrees celsius  Nonderated Continuous Voltage Rating And Type Per Section:  60.0 dc single section  Tolerance Range Per Section:
Between -55.0 degrees celsius and 85.0 degrees celsius  Nonderated Continuous Voltage Rating And Type Per Section:  60.0 dc single section  Tolerance Range Per Section:  -5.00/+5.00 percent single section
Between -55.0 degrees celsius and 85.0 degrees celsius  Nonderated Continuous Voltage Rating And Type Per Section: 60.0 dc single section  Tolerance Range Per Section: -5.00/+5.00 percent single section  Case Material:
Between -55.0 degrees celsius and 85.0 degrees celsius  Nonderated Continuous Voltage Rating And Type Per Section: 60.0 dc single section  Tolerance Range Per Section: -5.00/+5.00 percent single section  Case Material: Plastic
Between -55.0 degrees celsius and 85.0 degrees celsius  Nonderated Continuous Voltage Rating And Type Per Section: 60.0 dc single section  Tolerance Range Per Section: -5.00/+5.00 percent single section  Case Material: Plastic  Terminal Type And Quantity:
Between -55.0 degrees celsius and 85.0 degrees celsius  Nonderated Continuous Voltage Rating And Type Per Section: 60.0 dc single section  Tolerance Range Per Section: -5.00/+5.00 percent single section  Case Material: Plastic  Terminal Type And Quantity: 2 uninsulated wire lead
Between -55.0 degrees celsius and 85.0 degrees celsius  Nonderated Continuous Voltage Rating And Type Per Section:  60.0 dc single section  Tolerance Range Per Section: -5.00/+5.00 percent single section  Case Material:  Plastic  Terminal Type And Quantity: 2 uninsulated wire lead  Shelf Life:
Between -55.0 degrees celsius and 85.0 degrees celsius  Nonderated Continuous Voltage Rating And Type Per Section: 60.0 dc single section  Tolerance Range Per Section: -5.00/+5.00 percent single section  Case Material: Plastic  Terminal Type And Quantity: 2 uninsulated wire lead  Shelf Life: N/a
Between -55.0 degrees celsius and 85.0 degrees celsius  Nonderated Continuous Voltage Rating And Type Per Section: 60.0 dc single section  Tolerance Range Per Section: -5.00/+5.00 percent single section  Case Material: Plastic  Terminal Type And Quantity: 2 uninsulated wire lead  Shelf Life: N/a
Between -55.0 degrees celsius and 85.0 degrees celsius  Nonderated Continuous Voltage Rating And Type Per Section: 60.0 dc single section  Tolerance Range Per Section: -5.00/+5.00 percent single section  Case Material: Plastic  Terminal Type And Quantity: 2 uninsulated wire lead  Shelf Life: N/a  Unit Of Measure:
Between -55.0 degrees celsius and 85.0 degrees celsius  Nonderated Continuous Voltage Rating And Type Per Section: 60.0 dc single section  Tolerance Range Per Section: -5.00/+5.00 percent single section  Case Material: Plastic  Terminal Type And Quantity: 2 uninsulated wire lead  Shelf Life: N/a  Unit Of Measure:  Demilitarization: