## NSN 5910-00-994-6899



Electrolytic Fixed Capacitor - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5910-00-994-6899 **Body Style:** W/o mtg facilities, axial terminals Reliability Indicator: Not established **Terminal Length:** 2.500 inches **Body Diameter:** 0.687 inches **Body Length:** 3.750 inches **Terminal Diameter:** 0.032 inches **Schematic Diagram Designator:** Electrod (s) grounded to case, w/gnd terminal **Anode Type:** Plain foil **Impedance At Minimum Operating Tempurature In Ohms:** 5.2 **Electrical Polarization:** Polarized **Capacitance Value Per Section:** 760.000 microfarads single section **Nonderated Operating Temp:** Between -55.0 degrees celsius and 85.0 degrees celsius Dc Leakage At Maximum Operating Temp: 522.0 microamperes Nonderated Continuous Voltage Rating And Type Per Section: 40.0 dc single section **Tolerance Range Per Section:** -10.00/+75.00 percent single section Case Material: Metal **Capacitive Electrode Material:** Aluminum Dc Leakage At Reference Temp: 87.000 microamperes **Terminal Surface Treatment:** Solder **Case Insulation Material:** 

Plastic

Terminal Type And Quantity:
2 uninsulated wire lead

## NSN 5910-00-994-6899

Electrolytic Fixed Capacitor - Page 2 of 2



				-
C I	20	lŧ.	l i	fe:
J.	16		_,	ıc.

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A010b0