

View Online at <https://aerobasegroup.com/nsn/5910-00-994-7703>

Body Style:

W/thd bushing mtg, terminals on opposite endw/thd bushing mtg, terminals on opposite endw/thd bushing mtg, terminals on opposite end

Reliability Indicator:

Not establishednot establishednot established

Width Across Flats:

0.250 inches 0.250 inches 0.250 inches

Body Length:

0.469 inches

Schematic Diagram Designator:

Feedthrough

Mounting Facility Screw Thread Series Designator:

Uns

Mounting Facility Type And Quantity:

1 threaded bushing

Capacitance Value Per Section:

2500.000 picofarads single section

Voltage Temperature Limits Per Section In Percent Capacitance Change:

-66.0/+22.0 without voltage applied single section

Nonderated Operating Temp:

Between -55.0 degrees celsius and 85.0 degrees celsius

Thread Size:

0.216 inches

Nonderated Continuous Voltage Rating And Type Per Section:

500.0 dc single section

Tolerance Range Per Section:

-20.00/+20.00 percent single section

Case Material:

Metal

Insulation Resistance At Reference Temp:

7500.0 megohms

Power Factor At Reference Temperature In Percent:

2.5000

Terminal Surface Treatment:

Solder

Terminal Type And Quantity:

2 uninsulated wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A010b0