NSN 5910-00-995-1819

Ceramic Dielectric Fixed Capacitor - Page 1 of 1



radial terminals

| View Online at https://aerobasegroup.com/nsn/5910-00-995-1819 |
|---|
| Body Style: |
| W/o mtg facilities, radial terminalsw/o mtg facilities, radial terminalsw/o mtg facilities, |
| Reliability Indicator: |
| Not establishednot established |
| Terminal Length: |
| 1.500 inches 1.500 inches |
| Body Diameter: |
| 0.311 inches |
| Body Length: |
| 0.875 inches |
| Center To Center Distance Between Terminals Parallel To Length: |
| 0.500 inches |
| Terminal Diameter: |
| 0.025 inches |
| Schematic Diagram Designator: |
| No common or grounded electrode (s) |
| Capacitance Value Per Section: |
| 100.000 picofarads single section |
| Nonderated Operating Temp: |
| Between -55.0 degrees celsius and 85.0 degrees celsius |
| Tempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius: |
| -470.0 single section |
| Nonderated Continuous Voltage Rating And Type Per Section: |
| 500.0 dc single section |
| Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius: |
| -60.0/+60.0 single section |
| Tolerance Range Per Section: |
| -1.00/+1.00 percent single section |
| Case Material: |
| Plastic |
| Terminal Surface Treatment: |
| Solder |
| Terminal Type And Quantity: |
| 2 uninsulated wire lead |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |

Fiig:

A010b0