

View Online at <https://aerobasegroup.com/nsn/5910-00-996-0997>

Body Style:

W/thd bushing mtg, terminals on opposite endw/thd bushing mtg, terminals on opposite endw/thd bushing mtg, terminals on opposite end

Reliability Indicator:

Not establishednot establishednot established

Width Across Flats:

0.375 inches 0.375 inches 0.375 inches

Terminal Length:

0.437 inches 0.437 inches 0.437 inches

Body Length:

0.875 inches

Terminal Diameter:

0.051 inches

Schematic Diagram Designator:

Feedthrough

Mounting Facility Screw Thread Series Designator:

Unf

Mounting Facility Type And Quantity:

1 threaded bushing

Capacitance Value Per Section:

3300.000 picofarads single section

Voltage Temperature Limits Per Section In Percent Capacitance Change:

-82.0/+22.0 with rated voltage applied single section

Nonderated Operating Temp:

Between -55.0 degrees celsius and 85.0 degrees celsius

Thread Size:

0.313 inches

Nonderated Continuous Voltage Rating And Type Per Section:

1000.0 dc single section

Tolerance Range Per Section:

-20.00/+80.00 percent single section

Case Material:

Metal

Terminal Surface Treatment:

Solder

Terminal Type And Quantity:

2 uninsulated wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A010b0