

View Online at <https://aerobasegroup.com/nsn/5910-00-998-6935>

### Body Style:

W/o mtg facilities terminal (s) on one surfacew/o mtg facilities terminal(s) on one surfacew/o mtg facilities terminal(s) on one surface

### Reliability Indicator:

Not establishednot establishednot established

### Terminal Length:

1.500 inches 1.500 inches 1.500 inches

### Body Length:

0.200 inches

### Body Width:

0.200 inches

### Body Height:

0.100 inches

### Center To Center Distance Between Terminals Parallel To Length:

Between 0.100 inches and 0.200 inches

### Schematic Diagram Designator:

No common or grounded electrode (s)

### Capacitance Value Per Section:

27.000 picofarads single section

### Voltage Temperature Limits Per Section In Percent Capacitance Change:

-5.0/+5.0 without voltage applied single section

### Nonderated Operating Temp:

Between -55.0 degrees celsius and 125.0 degrees celsius

### Temperature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius:

0.0 single section

### Nonderated Continuous Voltage Rating And Type Per Section:

100.0 dc single section

### Tolerance Of Temperature Coefficient Per Section In Ppm Per Deg Celsius:

-30.0/+30.0 single section

### Tolerance Range Per Section:

-5.00/+5.00 percent single section

### Case Material:

Plastic

### Dissipation Factor At Reference Temperature In Percent:

0.2000

### Test Data Document:

28528-2432850g20 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

### Terminal Type And Quantity:

2 uninsulated wire lead

### Shelf Life:

N/a

### Unit Of Measure:

--

**Demilitarization:**

No

**Fiig:**

A010b0