

View Online at <https://aerobasegroup.com/nsn/5910-00-998-6940>

**Body Style:**

W/o mtg facilities terminal (s) on one surface/w/o mtg facilities terminal(s) on one surface/w/o mtg facilities terminal(s) on one surface

**Reliability Indicator:**

Not established/not established/not established

**Terminal Length:**

1.500 inches

**Body Length:**

0.300 inches

**Body Width:**

0.300 inches

**Body Height:**

0.100 inches

**Center To Center Distance Between Terminals Parallel To Length:**

Between 0.190 inches and 0.210 inches

**Schematic Diagram Designator:**

No common or grounded electrode (s)

**Capacitance Value Per Section:**

1000.000 picofarads single section

**Voltage Temperature Limits Per Section In Percent Capacitance Change:**

-5.0/+5.0 without voltage applied single section

**Nonderated Operating Temp:**

Between -55.0 degrees celsius and 125.0 degrees celsius

**Temperature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius:**

0.0 single section

**Nonderated Continuous Voltage Rating And Type Per Section:**

100.0 dc single section

**Tolerance Of Temperature Coefficient Per Section In Ppm Per Deg Celsius:**

-30.0/+30.0 single section

**Tolerance Range Per Section:**

-10.00/+10.00 percent single section

**Case Material:**

Plastic

**Dissipation Factor At Reference Temperature In Percent:**

0.2000

**Test Data Document:**

28528-2432850g8 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

**Terminal Type And Quantity:**

2 uninsulated wire lead

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A010b0