

View Online at <https://aerobasegroup.com/nsn/5910-00-998-7447>

Body Style:

W/thd mtg bushing, terminals on opposite ends/w/thd mtg bushing, terminals on opposite ends/w/thd mtg bushing, terminals on opposite ends

Reliability Indicator:

Not established/not established/not established

Width Across Flats:

0.312 inches 0.312 inches 0.312 inches

Terminal Length:

0.375 inches 0.375 inches 0.375 inches

Body Length:

0.750 inches

Terminal Diameter:

0.051 inches

Schematic Diagram Designator:

Feedthrough

Mounting Facility Screw Thread Series Designator:

Unf

Mounting Facility Type And Quantity:

1 threaded bushing

Capacitance Value Per Section:

1000.000 picofarads single section

Voltage Temperature Limits Per Section In Percent Capacitance Change:

-22.0/+22.0 with 500 volts applied single section

Nonrated Operating Temp:

Between -55.0 degrees celsius and 85.0 degrees celsius

Thread Size:

0.250 inches

Nonrated Continuous Voltage Rating And Type Per Section:

1000.0 dc single section

Tolerance Range Per Section:

-20.00/+80.00 percent single section

Case Material:

Metal

Insulation Resistance At Reference Temp:

20000.0 megohms

Power Factor At Reference Temperature In Percent:

2.0000

Terminal Surface Treatment:

Solder

Terminal Type And Quantity:

2 wire hook/loop

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A010b0