

View Online at <https://aerobasegroup.com/nsn/5910-00-998-9006>

Body Style:

W/thd mtg bushing, terminals on opposite ends/w/thd mtg bushing, terminals on opposite ends/w/thd mtg bushing, terminals on opposite ends

Reliability Indicator:

Not established/not established/not established

Width Across Flats:

0.250 inches 0.250 inches 0.250 inches

Terminal Length:

0.750 inches 0.750 inches

Body Length:

0.312 inches

Terminal Diameter:

0.040 inches

Schematic Diagram Designator:

Feedthrough

Mounting Facility Screw Thread Series Designator:

Unc

Mounting Facility Type And Quantity:

1 threaded bushing

Capacitance Value Per Section:

2000.000 picofarads single section

Voltage Temperature Limits Per Section In Percent Capacitance Change:

-15.0/+15.0 without voltage applied single section

Nonrated Operating Temp:

Between -55.0 degrees celsius and 125.0 degrees celsius

Thread Size:

0.164 inches

Nonrated Continuous Voltage Rating And Type Per Section:

100.0 dc single section

Tolerance Range Per Section:

-10.00/+10.00 percent single section

Case Material:

Metal

Insulation Resistance At Reference Temp:

18000.0 megohms

Dissipation Factor At Reference Temperature In Percent:

0.6000

Terminal Surface Treatment:

Solder

Terminal Type And Quantity:

2 uninsulated wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A010b0