## NSN 5910-00-998-9134

Electrolytic Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-998-9134

## **Body Style:**

W/o mtg facilities, terminal (s) on one end

## **Reliability Indicator:**

Not established

## Body Diameter:

1.375 inches

### **Body Length:**

3.500 inches

#### Schematic Diagram Designator:

No common or grounded electrode (s)

#### Anode Type:

Plain foil

### Impedance At Minimum Operating Tempurature In Ohms:

#### 6.7

**Electrical Polarization:** 

Polarized

#### **Capacitance Value Per Section:**

2200.000 microfarads single section

## Nonderated Operating Temp:

Between -40.0 degrees celsius and 85.0 degrees celsius

## Nonderated Continuous Voltage Rating And Type Per Section:

25.0 dc single section

## **Tolerance Range Per Section:**

-10.00/+100.00 percent single section

#### **Case Material:**

Metal

**Capacitive Electrode Material:** 

Aluminum

**Dissipation Factor At Reference Tempurature In Percent:** 

20.0000

Dc Leakage At Reference Temp:

352.000 microamperes

#### **Terminal Surface Treatment:**

Nickel

## Test Data Document:

81349-mil-c-62/8 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

## Terminal Type And Quantity:

4 pin

Shelf Life:

N/a

### Unit Of Measure:

# NSN 5910-00-998-9134

Electrolytic Fixed Capacitor - Page 2 of 2



Demilitarization:

No

Fiig:

A010b0