NSN 5910-01-004-2653

Plastic Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-004-2653

Body Style: W/o mtg facilities, terminal (s) on one surface **Reliability Indicator:** Not established **Body Length:** 2.500 inches **Body Width:** 1.188 inches **Body Height:** 3.500 inches **Terminal Diameter:** 0.216 inches **Terminal Height From Body:** 1.750 inches **Schematic Diagram Designator:** No common or grounded electrode (s) **Internal Electrical Connection Type:** Extended foil **Features Provided:** Hermetically sealed case **Insulation Resistance At Maximum Operating Temp:** 15.0 megohm-microfarads **Capacitance Value Per Section:** 1.000 microfarads single section **Nonderated Operating Temp:** Between -55.0 degrees celsius and 85.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 2000.0 dc single section **Tolerance Range Per Section:** -10.00/+10.00 percent single section **Case Material:** Metal **Insulation Resistance At Reference Temp:** 1500.0 megohm-microfarads **Dissipation Factor At Reference Tempurature In Percent:** 1.0000 **Dielectric Material:**

Test Data Document:

81349-mil-c-19978 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

Paper and plastic polyethylene terephthalate

2 standoff, threaded stud

NSN 5910-01-004-2653

Plastic Dielectric Fixed Capacitor - Page 2 of 2



Spec	ifica	ation	Data:
------	-------	-------	-------

81349-mil-c-19978/3 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A010b0