## NSN 5910-01-004-6119

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5910-01-004-6119

Body Style:
W/o mtg facilities terminal (s) on one surface
Reliability Indicator:
Not established
Terminal Length:
1.500 inches
Body Length:
0.820 inches
Body Width:
0.540 inches
Body Height:
0.390 inches
Terminal Diameter:
0.025 inches
Schematic Diagram Designator:
No common or grounded electrode (s)
Capacitance Value Per Section:
0.150 microfarads single section
Nonderated Operating Temp:
Between -55.0 degrees celsius and 125.0 degrees celsius
Nonderated Continuous Voltage Rating And Type Per Section:
Nonderated Continuous Voltage Rating And Type Per Section: 400.0 dc single section
400.0 dc single section
400.0 dc single section  Tolerance Range Per Section:
400.0 dc single section  Tolerance Range Per Section: -10.00/+10.00 percent single section
400.0 dc single section  Tolerance Range Per Section: -10.00/+10.00 percent single section  Case Material:
400.0 dc single section  Tolerance Range Per Section: -10.00/+10.00 percent single section  Case Material: Plastic
400.0 dc single section  Tolerance Range Per Section: -10.00/+10.00 percent single section  Case Material: Plastic  Insulation Resistance At Reference Temp:
400.0 dc single section  Tolerance Range Per Section: -10.00/+10.00 percent single section  Case Material: Plastic Insulation Resistance At Reference Temp: 1500.0 megohms
400.0 dc single section  Tolerance Range Per Section: -10.00/+10.00 percent single section  Case Material: Plastic Insulation Resistance At Reference Temp: 1500.0 megohms  Dissipation Factor At Reference Tempurature In Percent:
400.0 dc single section  Tolerance Range Per Section: -10.00/+10.00 percent single section  Case Material: Plastic Insulation Resistance At Reference Temp: 1500.0 megohms  Dissipation Factor At Reference Tempurature In Percent: 0.5000
400.0 dc single section  Tolerance Range Per Section: -10.00/+10.00 percent single section  Case Material: Plastic Insulation Resistance At Reference Temp: 1500.0 megohms  Dissipation Factor At Reference Tempurature In Percent: 0.5000  Terminal Type And Quantity:
400.0 dc single section  Tolerance Range Per Section: -10.00/+10.00 percent single section  Case Material: Plastic Insulation Resistance At Reference Temp: 1500.0 megohms  Dissipation Factor At Reference Tempurature In Percent: 0.5000  Terminal Type And Quantity: 2 uninsulated wire lead
400.0 dc single section  Tolerance Range Per Section: -10.00/+10.00 percent single section  Case Material: Plastic Insulation Resistance At Reference Temp: 1500.0 megohms  Dissipation Factor At Reference Tempurature In Percent: 0.5000  Terminal Type And Quantity: 2 uninsulated wire lead  Shelf Life:
400.0 dc single section  Tolerance Range Per Section: -10.00/+10.00 percent single section  Case Material: Plastic Insulation Resistance At Reference Temp: 1500.0 megohms  Dissipation Factor At Reference Tempurature In Percent: 0.5000  Terminal Type And Quantity: 2 uninsulated wire lead  Shelf Life: N/a
400.0 dc single section  Tolerance Range Per Section: -10.00/+10.00 percent single section  Case Material: Plastic Insulation Resistance At Reference Temp: 1500.0 megohms  Dissipation Factor At Reference Tempurature In Percent: 0.5000  Terminal Type And Quantity: 2 uninsulated wire lead  Shelf Life: N/a
Tolerance Range Per Section: -10.00/+10.00 percent single section  Case Material: Plastic Insulation Resistance At Reference Temp: 1500.0 megohms Dissipation Factor At Reference Tempurature In Percent: 0.5000 Terminal Type And Quantity: 2 uninsulated wire lead Shelf Life: N/a Unit Of Measure:
Tolerance Range Per Section: -10.00/+10.00 percent single section  Case Material: Plastic Insulation Resistance At Reference Temp: 1500.0 megohms Dissipation Factor At Reference Tempurature In Percent: 0.5000 Terminal Type And Quantity: 2 uninsulated wire lead Shelf Life: N/a Unit Of Measure: Demilitarization: