NSN 5910-01-004-6302

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-004-6302 **Body Style:** W/o mtg facilities, axial terminals **Reliability Indicator:** Established **Terminal Length:** 1.500 inches **Body Diameter:** 0.432 inches **Body Length:** 1.125 inches **Terminal Diameter:** 0.040 inches **Schematic Diagram Designator:** No common or grounded electrode (s) **Features Provided:** Hermetically sealed case **Capacitance Value Per Section:** 1.000 microfarads single section **Nonderated Operating Temp:** Between -55.0 degrees celsius and 85.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 50.0 dc single section **Tolerance Range Per Section:** -10.00/+10.00 percent single section Case Material: Metal **Insulation Resistance At Reference Temp:** 10000.0 megohms **Dissipation Factor At Reference Tempurature In Percent:** 0.3000 **Case Insulation Material:** Plastic **Test Data Document:** 81349-milc39022/1 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). **Terminal Type And Quantity:** 2 uninsulated wire lead Shelf Life: N/a **Unit Of Measure:**

No

Demilitarization:

NSN 5910-01-004-6302

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 2 of 2



Fiig:

A010b0