NSN 5910-01-004-9980

Electrolytic Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-004-9980

Body Style:
W/o mtg facilities, terminal (s) on one end
Reliability Indicator:
Not established
Terminal Length:
0.281 inches
Body Diameter:
3.000 inches
Body Length:
5.633 inches
Center To Center Distance Between Terminals Parallel To Diameter:
1.250 inches
Terminal Diameter:
0.190 inches
Schematic Diagram Designator:
No common or grounded electrode (s)
Electrical Polarization:
Nonpolarized
End Application:
Kidd class ddg, emory s. Land class as, ticonderoga class cg (47), spruance class dd (963), tarawa class lha, nimitz class cvn. 2m/ate
microminiature automatic test equipment.
Capacitance Value Per Section:
38500.000 picofarads single section
Nonderated Operating Temp:
Between -40.0 degrees celsius and 85.0 degrees celsius
Nonderated Continuous Voltage Rating And Type Per Section:
75.0 dc single section
Criticality Code Justification:
Feat
Tolerance Range Per Section:
-10.00/+75.00 percent single section
Case Material:
Metal
Capacitive Electrode Material:
Aluminum
Equivalent Series Resistance At Reference Tempurature In Ohms:
0.014
Case Insulation Material:
Plastic
Special Features

2 threaded hole

Weapon system essential Terminal Type And Quantity:

NSN 5910-01-004-9980

Electrolytic Fixed Capacitor - Page 2 of 2



She	lf I	Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A010b0