NSN 5910-01-006-0105

Paper and plastic polyethylene terephthalate

Test Data Document:

Body Style:

Plastic Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-006-0105

W/o mtg facilities, terminal (s) on one surface
Reliability Indicator:
Not established
Body Length:
1.812 inches
Body Width:
1.062 inches
Body Height:
2.875 inches
Center To Center Distance Between Terminals Parallel To Length:
0.812 inches
Terminal Diameter:
0.216 inches
Terminal Height From Body:
1.375 inches
Schematic Diagram Designator:
No common or grounded electrode (s)
Internal Electrical Connection Type:
Extended foil
Features Provided:
Hermetically sealed case
Insulation Resistance At Maximum Operating Temp:
20.0 megohm-microfarads
Capacitance Value Per Section:
oupuniance value i or occinent
1.000 microfarads single section
1.000 microfarads single section
1.000 microfarads single section Nonderated Operating Temp:
1.000 microfarads single section Nonderated Operating Temp: Between -65.0 degrees celsius and 125.0 degrees celsius
1.000 microfarads single section Nonderated Operating Temp: Between -65.0 degrees celsius and 125.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section:
1.000 microfarads single section Nonderated Operating Temp: Between -65.0 degrees celsius and 125.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 600.0 dc single section
1.000 microfarads single section Nonderated Operating Temp: Between -65.0 degrees celsius and 125.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 600.0 dc single section Tolerance Range Per Section:
1.000 microfarads single section Nonderated Operating Temp: Between -65.0 degrees celsius and 125.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 600.0 dc single section Tolerance Range Per Section: -10.00/+10.00 percent single section
1.000 microfarads single section Nonderated Operating Temp: Between -65.0 degrees celsius and 125.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 600.0 dc single section Tolerance Range Per Section: -10.00/+10.00 percent single section Case Material:
1.000 microfarads single section Nonderated Operating Temp: Between -65.0 degrees celsius and 125.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 600.0 dc single section Tolerance Range Per Section: -10.00/+10.00 percent single section Case Material: Metal
1.000 microfarads single section Nonderated Operating Temp: Between -65.0 degrees celsius and 125.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 600.0 dc single section Tolerance Range Per Section: -10.00/+10.00 percent single section Case Material: Metal Insulation Resistance At Reference Temp:
1.000 microfarads single section Nonderated Operating Temp: Between -65.0 degrees celsius and 125.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 600.0 dc single section Tolerance Range Per Section: -10.00/+10.00 percent single section Case Material: Metal Insulation Resistance At Reference Temp: 15000.0 megohm-microfarads

81349-mil-c-19978 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

NSN 5910-01-006-0105

Plastic Dielectric Fixed Capacitor - Page 2 of 2



Terminal Type And Quantity:
2 standoff, threaded stud
Specification Data:
81349-mil-c-19978/3 government specification
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A010b0