NSN 5910-01-007-1522

Ceramic Dielectric Fixed Capacitor - Page 1 of 2



radial terminals

View Online at https://aerobasegroup.com/nsn/5910-01-007-1522

Body Style:
W/o mtg facilities, radial terminalsw/o mtg facilities, radial terminalsw/o mtg facilities,
Reliability Indicator:
Not establishednot established
Terminal Length:
1.250 inches 1.250 inches 1.250 inches
Body Diameter:
0.200 inches
Body Length:
0.400 inches
Center To Center Distance Between Terminals Parallel To Length:
0.250 inches
Terminal Diameter:
0.025 inches
Schematic Diagram Designator:
No common or grounded electrode (s)
Capacitance Value Per Section:
10.000 picofarads single section
Nonderated Operating Temp:
Between -55.0 degrees celsius and 85.0 degrees celsius
Tempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius:
-5600.0 single section
Nonderated Continuous Voltage Rating And Type Per Section:
500.0 dc single section
Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius:
-1000.0/+1000.0 single section
Tolerance Range Per Section:
-0.50/+0.50 picofarads single section
Case Material:
Ceramic
Insulation Resistance At Reference Temp:
10000.0 megohms
Terminal Surface Treatment:
Solder
Terminal Type And Quantity:
2 uninsulated wire lead
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

No

NSN 5910-01-007-1522

Ceramic Dielectric Fixed Capacitor - Page 2 of 2



Fiig:

A010b0