## NSN 5910-01-007-8768

Electrolytic Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-007-8768

Body	Stv	le٠
Bouv	JLV	ıc.

W/o mtg facilities terminal (s) on one surface

**Reliability Indicator:** 

Not established

**Terminal Length:** 

1.250 inches

**Body Length:** 

0.500 inches

**Body Width:** 

0.375 inches

0.070 11101103

**Body Height:** 

0.195 inches

**Center To Center Distance Between Terminals Parallel To Length:** 

0.400 inches

**Terminal Diameter:** 

0.025 inches

**Schematic Diagram Designator:** 

No common or grounded electrode (s)

**Electrical Polarization:** 

Polarized

**Capacitance Value Per Section:** 

4.700 microfarads single section

**Nonderated Operating Temp:** 

Between -55.0 degrees celsius and 85.0 degrees celsius

Dc Leakage At Maximum Operating Temp:

10.0 microamperes

Nonderated Continuous Voltage Rating And Type Per Section:

20.0 dc single section

**Tolerance Range Per Section:** 

-5.00/+5.00 percent single section

**Case Material:** 

Plastic

**Capacitive Electrode Material:** 

Tantalum

**Dissipation Factor At Reference Tempurature In Percent:** 

6.0000

Dc Leakage At Reference Temp:

1.000 microamperes

**Terminal Surface Treatment:** 

Solder

**Terminal Type And Quantity:** 

2 uninsulated wire lead

## NSN 5910-01-007-8768

Electrolytic Fixed Capacitor - Page 2 of 2



_			•		
•	n	ο.	•	18	e:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A010b0