# NSN 5910-01-008-5060

Ceramic Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-008-5060

<b>D</b> -	٠. د	C4	٠
DU	uv	Stv	ıe:

W/o mtg facilities, terminals on opposite surfacesw/o mtg facilities on opposite surfacesw/o mtg facilities, terminals on opposite surfacesw/o mtg facilities on

# **Reliability Indicator:**

Not establishednot established

#### **Terminal Length:**

0.875 inches 0.875 inches 0.875 inches

**Body Length:** 

0.140 inches

**Body Width:** 

0.062 inches

**Body Height:** 

0.140 inches

**Terminal Diameter:** 

0.023 inches

# **Schematic Diagram Designator:**

No common or grounded electrode (s)

# **Insulation Resistance At Maximum Operating Temp:**

100000.0 megohms

# **Capacitance Value Per Section:**

100.000 picofarads single section

### **Nonderated Operating Temp:**

Between -55.0 degrees celsius and 125.0 degrees celsius

# Tempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius:

95.0 single section

# Nonderated Continuous Voltage Rating And Type Per Section:

300.0 dc single section

# Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius:

-20.0/+20.0 single section

#### **Tolerance Range Per Section:**

-1.00/+1.00 percent single section

# **Case Material:**

Glass

### **Insulation Resistance At Reference Temp:**

1000000.0 megohms

# **Dissipation Factor At Reference Tempurature In Percent:**

0.0002

# **Terminal Surface Treatment:**

Silver

### **Terminal Type And Quantity:**

2 uninsulated wire lead

# Shelf Life:

N/a

# NSN 5910-01-008-5060

Ceramic Dielectric Fixed Capacitor - Page 2 of 2



		• •			
ш	ın	10	<i>(</i> )+	Measure:	

--

Demilitarization:

No

Fiig:

A010b0