NSN 5910-01-009-5583



Plastic Dielectric Fixed Capacitor - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5910-01-009-5583 **Body Style:** W/o mtg facilities terminal (s) on one surface **Reliability Indicator:** Not established **Terminal Length:** 1.500 inches **Body Length:** 0.790 inches **Body Width:** 0.420 inches **Body Height:** 0.250 inches Center To Center Distance Between Terminals Parallel To Length: 0.375 inches **Terminal Diameter:** 0.032 inches **Schematic Diagram Designator:** No common or grounded electrode (s) **Insulation Resistance At Maximum Operating Temp:** 20.0 megohm-microfarads **Capacitance Value Per Section:** 1200.000 picofarads single section **Nonderated Operating Temp:** Between -55.0 degrees celsius and 125.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 100.0 dc single section **Tolerance Range Per Section:** -10.00/+10.00 percent single section **Case Material: Plastic Insulation Resistance At Reference Temp:** 20000.0 megohm-microfarads **Power Factor At Reference Tempurature In Percent:** 0.6000 **Terminal Surface Treatment:** Solder **Dielectric Material:** Plastic polyethylene terephthalate

Terminal Type And Quantity:

2 uninsulated wire lead

Shelf Life:

N/a

NSN 5910-01-009-5583

Plastic Dielectric Fixed Capacitor - Page 2 of 2



| ш | ın | 10 | <i>(</i>)+ | Measure: | |
|---|----|----|-------------|----------|--|
| | | | | | |

--

Demilitarization:

No

Fiig:

A010b0