NSN 5910-01-010-1612

Air Dielectric Variable Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-010-1612 **Thread Class:** 2a **Body Style:** Piston **Overall Length:** 0.469 inches **Bushing Diameter:** 0.234 inches **Bushing Length:** 0.077 inches **Body Length:** 0.313 inches **Overall Diameter:** 0.281 inches Tempurature Coefficient Of Capacitance In Ppm Per Deg Celsius: 0.0 single section **Tolerance Of Tempurature Coefficient In Ppm Per Deg Celsius:** -75.0/+75.0 single section **Quality Factor At 25 Deg Celsius:** 2000.0 **Terminal Thickness:** 0.015 inches **Mounting Facility Screw Thread Series Designator:** Uns **Inclosure Type:** Encased **Tuning Characteristic:** Straight line capacity single section **Adjustment Device Torque:** Between 0.500 inch-ounces and 5.000 inch-ounces **Bushing Shape:** Insulation Dc Resistance At 25 Deg Celsius: 1000.0 gigohms **Mounting Facility Type And Quantity:** 1 threaded bushing Thready Qty Per Inch (tpi): 64 **Nonderated Operating Temp:** Between -65.0 degrees celsius and 125.0 degrees celsius

Thread Size:

0.234 inches

NSN 5910-01-010-1612

Air Dielectric Variable Capacitor - Page 2 of 2



Capacitance Range In Picofarads: +1.0/+10.0 single section Nonderated Voltage Rating And Type: 200.0 dc continuous single section Adjustment Device Drive Type And Quantity: 1 slotted screw Terminal Type And Quantity: 2 tab, solder lug Shelf Life: N/a Unit Of Measure: -- Demilitarization: No

Fiig: A096a0