Plastic Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-010-2902

## **Body Style:**

W/o mtg facilities, axial terminals

**Reliability Indicator:** 

Not established

**Terminal Length:** 

1.500 inches

### **Body Diameter:**

0.400 inches

**Body Length:** 

0.600 inches

**Terminal Diameter:** 

0.025 inches

Schematic Diagram Designator:

No common or grounded electrode (s)

### **Internal Electrical Connection Type:**

Extended foil

**End Application:** 

Strategic weapon systems (poseidon and trident).

### **Capacitance Value Per Section:**

0.022 microfarads single section

## Nonderated Operating Temp:

Between -55.0 degrees celsius and 85.0 degrees celsius

## Tempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius:

-150.0 single section

### Nonderated Continuous Voltage Rating And Type Per Section:

63.0 dc single section

### Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius:

-80.0/+80.0 single section

### **Tolerance Range Per Section:**

-1.00/+1.00 percent single section

### Case Material:

Metal

# **Terminal Surface Treatment:**

Solder

# Dielectric Material:

Plastic polystyrene

# Terminal Type And Quantity:

2 uninsulated wire lead

Shelf Life:

N/a

# Unit Of Measure:

---

Plastic Dielectric Fixed Capacitor - Page 2 of 2



Demilitarization:

No

Fiig:

A010b0