NSN 5910-01-010-5320

Ceramic Dielectric Fixed Capacitor - Page 1 of 2



| view Online at https://aerobasegroup.com/nsn/5910-01-010-5320 |
|---|
| Unable To Decode: |
| W/o mtg facilities terminal (s) on one surfacew/o mtg facilities terminal(s) on one surfacew/o mtg facilities terminal(s) on one surfacew |
| Reliability Indicator: |
| Not establishednot established |
| Terminal Length: |
| 0.593 inches 0.593 inches 0.593 inches |
| Body Length: |
| 0.234 inches |
| Body Width: |
| 0.312 inches |
| Body Height: |
| 0.080 inches |
| Center To Center Distance Between Terminals Parallel To Length: |
| 0.203 inches |
| Terminal Diameter: |
| 0.024 inches |
| Schematic Diagram Designator: |
| No common or grounded electrode (s) |
| Capacitance Value Per Section: |
| 82.000 picofarads single section |
| Nonderated Operating Temp: |
| Between -55.0 degrees celsius and 85.0 degrees celsius |
| Tempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius: |
| 0.0 single section |
| Nonderated Continuous Voltage Rating And Type Per Section: |
| 100.0 dc single section |
| Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius: |
| -40.0/+40.0 single section |
| Tolerance Range Per Section: |
| -2.00/+2.00 percent single section |
| Case Material: |
| Plastic |
| Insulation Resistance At Reference Temp: |
| 1000.0 megohms |
| Terminal Type And Quantity: |
| 2 uninsulated wire lead |
| Shelf Life: |
| N/a |
| Unit Of Measure: |

No

Demilitarization:

NSN 5910-01-010-5320

Ceramic Dielectric Fixed Capacitor - Page 2 of 2



Fiig:

A010b0