NSN 5910-01-010-9530 Electrolytic Fixed Capacitor - Page 1 of 2



| View Online at https://aerobasegroup.com/nsn/5910-01-010-9530 |
|--|
| Body Style: |
| W/o mtg facilities, axial terminals |
| Reliability Indicator: |
| Not established |
| Terminal Length: |
| 2.500 inches |
| Body Diameter: |
| 0.875 inches |
| Body Length: |
| 1.125 inches |
| Terminal Diameter: |
| 0.040 inches |
| Schematic Diagram Designator: |
| Electrod (s) grounded to case, w/gnd terminal |
| Electrical Polarization: |
| Polarized |
| Capacitance Value Per Section: |
| 220.000 microfarads single section |
| Nonderated Operating Temp: |
| Between -55.0 degrees celsius and 85.0 degrees celsius |
| Nonderated Continuous Voltage Rating And Type Per Section: |
| 50.0 dc single section |
| Tolerance Range Per Section: |
| -10.00/+75.00 percent single section |
| Case Material: |
| Metal |
| Capacitive Electrode Material: |
| Aluminum |
| Dissipation Factor At Reference Tempurature In Percent: |
| 10.0000 |
| Dc Leakage At Reference Temp: |
| 55.000 microamperes |
| Case Insulation Material: |
| Plastic |
| Test Data Document: |
| 81349-milc39018/3 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification |
| format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain |
| environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). |
| Terminal Type And Quantity: |
| 2 uninsulated wire lead |
| Shelf Life: |
| N/α |

Unit Of Measure:

NSN 5910-01-010-9530

Electrolytic Fixed Capacitor - Page 2 of 2



Demilitarization:

No

Fiig:

A010b0