## NSN 5910-01-011-9219

Electrolytic Fixed Capacitor - Page 1 of 2



Body Style:
W/o mtg facilities terminal (s) on one surface
Reliability Indicator:
Not established
Terminal Length:
1.625 inches
Body Length:
0.190 inches
Body Width:
0.235 inches
Body Height:
0.105 inches
Center To Center Distance Between Terminals Parallel To Length:
0.125 inches
Terminal Diameter:
0.010 inches
Schematic Diagram Designator:
No common or grounded electrode (s)
Anode Type:
Solid
Electrical Polarization:
Nonpolarized
Capacitance Value Per Section:
1.000 microfarads single section
Nonderated Operating Temp:
Between -55.0 degrees celsius and 85.0 degrees celsius
Nonderated Continuous Voltage Rating And Type Per Section:
20.0 dc single section
Tolerance Range Per Section:
-10.00/+10.00 percent single section
Case Material:
Plastic
Capacitive Electrode Material:
Tantalum
Dissipation Factor At Reference Tempurature In Percent:
6.0000
Dc Leakage At Reference Temp:
1.000 microamperes
Terminal Surface Treatment:
1.000 microfarads single section  Nonderated Operating Temp:
· ·
·
Nonderated Operating Temp:
Between -55.0 degrees celsius and 85.0 degrees celsius
•
Capacitive Electrode Material:
Tantalum
•
Terminal Surface Treatment:

Solder

**Terminal Type And Quantity:** 

2 uninsulated wire lead

## NSN 5910-01-011-9219

Electrolytic Fixed Capacitor - Page 2 of 2



She	lf	Life:	
Oile	••	LIIV.	

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A010b0