NSN 5910-01-012-2526

Electrolytic Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-012-2526

Body Style: W/o mtg facilities, axial terminals **Reliability Indicator:** Established **Terminal Length:** 1.500 inches **Body Diameter:** Between 0.170 inches and 0.201 inches **Body Length:** 0.474 inches **Terminal Diameter:** 0.020 inches **Schematic Diagram Designator:** Electrod (s) grounded to case, w/gnd terminal **Electrical Polarization:** Polarized **Features Provided:** Hermetically sealed case **Capacitance Value Per Section:** 1.500 microfarads single section **Nonderated Operating Temp:** Between -55.0 degrees celsius and 125.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 50.0 dc single section **Tolerance Range Per Section:** -20.00/+20.00 percent single section Case Material: Metal **Capacitive Electrode Material: Tantalum Dissipation Factor At Reference Tempurature In Percent:** Dc Leakage At Reference Temp: 0.600 microamperes **Case Insulation Material:** Plastic **Test Data Document:** 81349-mil-c-39003/1 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification

format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain

environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

2 uninsulated wire lead

Shelf Life:

N/a

NSN 5910-01-012-2526

Electrolytic Fixed Capacitor - Page 2 of 2



		eas	

--

Demilitarization:

No

Fiig:

A010b0