NSN 5910-01-012-2990

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-012-2990

view Online at https://aerobasegroup.com/hsh/5910-01-012-2990
Body Style:
W/thd mtg bushing, terminals on opposite ends
Reliability Indicator:
Not established
Width Across Flats:
1.000 inches
Terminal Length:
1.625 inches
Body Length:
2.625 inches
Terminal Diameter:
0.040 inches
Schematic Diagram Designator:
No common or grounded electrode (s)
Mounting Facility Screw Thread Series Designator:
Unf
Mounting Facility Type And Quantity:
1 threaded bushing
Insulation Resistance At Maximum Operating Temp:
1000.0 megohms
Capacitance Value Per Section:
10.000 microfarads single section
Nonderated Operating Temp:
Between -55.0 degrees celsius and 125.0 degrees celsius
Thread Size:
0.312 inches
Nonderated Continuous Voltage Rating And Type Per Section:
200.0 dc single section
Tolerance Range Per Section:
-20.00/+20.00 percent single section
Case Material:
Metal
Insulation Resistance At Reference Temp:
100000.0 megohms
Dissipation Factor At Reference Tempurature In Percent:
0.300
Terminal Surface Treatment:
Solder
Terminal Type And Quantity:
2 uninsulated wire lead
Shalf Life:

N/a

NSN 5910-01-012-2990

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 2 of 2



		• -						
ш	ın	ıt (r 1t	ΝЛ	മാ	CI.	ıre:	•

--

Demilitarization:

No

Fiig:

A010b0