NSN 5910-01-013-0844

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-013-0844

view Offline at https://defobasegroup.com/hsh/55/10-01-015-00-44
Body Style:
W/thd bushing mtg, terminals on opposite ends
Reliability Indicator:
Not established
Terminal Length:
0.281 inches
Body Diameter:
0.750 inches
Body Length:
2.125 inches
Continuous Current Rating In Amps:
10.0
Schematic Diagram Designator:
Feedthrough
Mounting Facility Screw Thread Series Designator:
Unf
Mounting Facility Type And Quantity:
1 threaded bushing
Features Provided:
Hermetically sealed case
Capacitance Value Per Section:
1.000 microfarads single section
Nonderated Operating Temp:
Between -55.0 degrees celsius and 125.0 degrees celsius
Thread Size:
0.500 inches
Nonderated Continuous Voltage Rating And Type Per Section:
400.0 dc single section
Tolerance Range Per Section:
-10.00/+10.00 percent single section
Case Material:
Metal
Insulation Resistance At Reference Temp:
50000.0 megohm-microfarads
Dissipation Factor At Reference Tempurature In Percent:
0.3000
Terminal Surface Treatment:
Solder
Terminal Type And Quantity:
2 tab, solder lug
Shelf Life:

N/a

NSN 5910-01-013-0844

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 2 of 2



		• -					
ш	ın	18 1	r 1+	Me	20	ıır	Δ.
u	,,,	IL	v.	IAIC	as	uı	┖.

--

Demilitarization:

No

Fiig:

A010b0