

View Online at <https://aerobasegroup.com/nsn/5910-01-013-2369>

Body Style:

W/o mtg facilities terminal (s) on one surfacew/o mtg facilities terminal(s) on one surfacew/o mtg facilities terminal(s) on one surface

Reliability Indicator:

Not establishednot establishednot established

Terminal Length:

1.250 inches 1.250 inches

Body Length:

Between 0.160 inches and 0.200 inches

Body Width:

Between 0.150 inches and 0.200 inches

Body Height:

0.125 inches

Center To Center Distance Between Terminals Parallel To Length:

Between 0.069 inches and 0.131 inches

Terminal Diameter:

Between 0.015 inches and 0.024 inches

Schematic Diagram Designator:

No common or grounded electrode (s)

Capacitance Value Per Section:

470.000 picofarads single section

Nonderated Operating Temp:

Between -55.0 degrees celsius and 125.0 degrees celsius

Tempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius:

0.0 single section

Nonderated Continuous Voltage Rating And Type Per Section:

50.0 dc single section

Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius:

-30.0/+30.0 single section

Tolerance Range Per Section:

-5.00/+5.00 percent single section

Case Material:

Plastic

Insulation Resistance At Reference Temp:

2500.0 megohm-microfarads

Quality Factor At Reference Temp:

1000.0000

Terminal Surface Treatment:

Solder

Terminal Type And Quantity:

2 uninsulated wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A010b0