NSN 5910-01-013-4413

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-013-4413

Body Style:

W/mtg tabs/flanges, terminal (s) on one surface

Reliability Indicator:

Not established

Terminal Length:

0.440 inches

Body Length:

Between 1.970 inches and 2.030 inches

Body Width:

Between 1.970 inches and 2.030 inches

Body Height:

2.380 inches

Unthreaded Mounting Hole Diameter:

Between 0.187 inches and 0.193 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

Between 2.550 inches and 2.570 inches

Schematic Diagram Designator:

No common or grounded electrode (s)

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

Between 1.490 inches and 1.510 inches

Mounting Facility Type And Quantity:

4 unthreaded mounting holes

Features Provided:

Hermetically sealed case

Capacitance Value Per Section:

25.000 microfarads single section

Nonderated Operating Temp:

Between -55.0 degrees celsius and 105.0 degrees celsius

Nonderated Continuous Voltage Rating And Type Per Section:

300.0 dc single section

Tolerance Range Per Section:

-10.00/+20.00 percent single section

Case Material:

Metal

Insulation Resistance At Reference Temp:

2000.0 megohms

Dissipation Factor At Reference Tempurature In Percent:

0.1500

Terminal Surface Treatment:

Solder

Terminal Type And Quantity:

2 tab, solder lug

NSN 5910-01-013-4413

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 2 of 2



Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A010b0