## NSN 5910-01-013-4413

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-013-4413

**Body Style:** 

W/mtg tabs/flanges, terminal (s) on one surface

Reliability Indicator:

Not established

**Terminal Length:** 

0.440 inches

**Body Length:** 

Between 1.970 inches and 2.030 inches

**Body Width:** 

Between 1.970 inches and 2.030 inches

**Body Height:** 

2.380 inches

**Unthreaded Mounting Hole Diameter:** 

Between 0.187 inches and 0.193 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

Between 2.550 inches and 2.570 inches

**Schematic Diagram Designator:** 

No common or grounded electrode (s)

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

Between 1.490 inches and 1.510 inches

**Mounting Facility Type And Quantity:** 

4 unthreaded mounting holes

**Features Provided:** 

Hermetically sealed case

Capacitance Value Per Section:

25.000 microfarads single section

**Nonderated Operating Temp:** 

Between -55.0 degrees celsius and 105.0 degrees celsius

Nonderated Continuous Voltage Rating And Type Per Section:

300.0 dc single section

**Tolerance Range Per Section:** 

-10.00/+20.00 percent single section

Case Material:

Metal

Insulation Resistance At Reference Temp:

2000.0 megohms

Dissipation Factor At Reference Tempurature In Percent:

0.1500

**Terminal Surface Treatment:** 

Solder

**Terminal Type And Quantity:** 

2 tab, solder lug

## NSN 5910-01-013-4413

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 2 of 2



Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A010b0