

View Online at <https://aerobasegroup.com/nsn/5910-01-013-5023>

**Body Style:**

Dual inlinedual inlinedual inline

**Reliability Indicator:**

Not establishednot establishednot established

**Terminal Length:**

Between 0.120 inches and 0.120 inches and 0.176 inches 0.176 inches

**Body Length:**

Between 0.787 inches and 0.795 inches

**Body Width:**

Between 0.290 inches and 0.310 inches

**Body Height:**

0.135 inches

**Center To Center Distance Between Terminals Parallel To Length:**

Between 0.690 inches and 0.710 inches

**Center To Center Distance Between Terminals Parallel To Width:**

Between 0.300 inches and 0.400 inches

**Schematic Diagram Designator:**

No common or grounded electrode (s)

**Section Quantity:**

8

**Capacitance Value Per Section:**

1500.000 picofarads all sections

**Voltage Tempurature Limits Per Section In Percent Capacitance Change:**

-15.0/+15.0 without voltage applied all sections

**Nonderated Operating Temp:**

Between -55.0 degrees celsius and 85.0 degrees celsius

**Nonderated Continuous Voltage Rating And Type Per Section:**

100.0 dc all sections

**Tolerance Range Per Section:**

-20.00/+20.00 percent all sections

**Case Material:**

Plastic

**Insulation Resistance At Reference Temp:**

100000.0 megohms

**Dissipation Factor At Reference Tempurature In Percent:**

2.5000

**Terminal Surface Treatment:**

Solder

**Terminal Type And Quantity:**

16 printed circuit

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A010b0