## NSN 5910-01-013-7076

Electrolytic Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-013-7076
Body Style:
W/o mtg facilities, axial terminals
Reliability Indicator:
Established
Terminal Length:
1.500 inches
Body Diameter:
0.219 inches
Body Length:
0.453 inches
Schematic Diagram Designator:
Electrod (s) grounded to case, w/gnd terminal
Electrical Polarization:
Polarized
Features Provided:
Hermetically sealed case
Capacitance Value Per Section:
10.000 microfarads single section
Nonderated Operating Temp:
Between -55.0 degrees celsius and 125.0 degrees celsius
Nonderated Continuous Voltage Rating And Type Per Section:
25.0 dc single section
Tolerance Range Per Section:
-20.00/+20.00 percent single section
Case Material:
Metal
Capacitive Electrode Material:
Tantalum
Dissipation Factor At Reference Tempurature In Percent:
4.6000
Dc Leakage At Reference Temp:
1.000 microamperes
Case Insulation Material:
Plastic
Test Data Document:
81349-milc39006 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Terminal Type And Quantity:
2 uninsulated wire lead
Shelf Life:

N/a

**Unit Of Measure:** 

## NSN 5910-01-013-7076

Electrolytic Fixed Capacitor - Page 2 of 2



Demi			

No

Fiig:

A010b0