NSN 5910-01-014-3276

Ceramic Dielectric Fixed Capacitor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5910-01-014-3276

| Body Style: |
|---|
| W/o mtg facilities, terminals on opposite surfacesw/o mtg facilities, terminals on opposite surfacesw/o mtg facilities, terminals on opposite |
| surfaces |
| Reliability Indicator: |
| Not establishednot established |
| Terminal Length: |
| 0.135 inches 0.135 inches 0.135 inches |
| Body Length: |
| 0.250 inches |
| Body Width: |
| 0.885 inches |
| Body Height: |
| 0.275 inches |
| Schematic Diagram Designator: |
| No common or grounded electrode (s) |
| Section Quantity: |
| 8 |
| Capacitance Value Per Section: |
| 0.100 microfarads all sections |
| Voltage Tempurature Limits Per Section In Percent Capacitance Change: |
| -15.0/+15.0 without voltage applied all sections |
| Nonderated Operating Temp: |
| Between -55.0 degrees celsius and 70.0 degrees celsius |
| Nonderated Continuous Voltage Rating And Type Per Section: |
| 100.0 dc all sections |
| Tolerance Range Per Section: |
| -20.00/+20.00 percent all sections |
| Case Material: |
| Plastic |
| Dissipation Factor At Reference Tempurature In Percent: |
| 4.0000 |
| Terminal Surface Treatment: |
| Nickel |
| Terminal Type And Quantity: |
| 16 tab, solder lug |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |

Fiig: A010b0

No