



View Online at <https://aerobasegroup.com/nsn/5910-01-014-3276>

<b>Body Style:</b>	W/o mtg facilities, terminals on opposite surfacesw/o mtg facilities, terminals on opposite surfacesw/o mtg facilities, terminals on opposite surfaces
<b>Reliability Indicator:</b>	Not establishednot establishednot established
<b>Terminal Length:</b>	0.135 inches 0.135 inches 0.135 inches
<b>Body Length:</b>	0.250 inches
<b>Body Width:</b>	0.885 inches
<b>Body Height:</b>	0.275 inches
<b>Schematic Diagram Designator:</b>	No common or grounded electrode (s)
<b>Section Quantity:</b>	8
<b>Capacitance Value Per Section:</b>	0.100 microfarads all sections
<b>Voltage Tempurature Limits Per Section In Percent Capacitance Change:</b>	-15.0/+15.0 without voltage applied all sections
<b>Nonderated Operating Temp:</b>	Between -55.0 degrees celsius and 70.0 degrees celsius
<b>Nonderated Continuous Voltage Rating And Type Per Section:</b>	100.0 dc all sections
<b>Tolerance Range Per Section:</b>	-20.00/+20.00 percent all sections
<b>Case Material:</b>	Plastic
<b>Dissipation Factor At Reference Tempurature In Percent:</b>	4.0000
<b>Terminal Surface Treatment:</b>	Nickel
<b>Terminal Type And Quantity:</b>	16 tab, solder lug
<b>Shelf Life:</b>	N/a
<b>Unit Of Measure:</b>	--
<b>Demilitarization:</b>	No
<b>Fiig:</b>	A010b0