NSN 5910-01-014-6443

Electrolytic Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-014-6443

Body Style:
W/o mtg facilities terminal (s) on one surface
Reliability Indicator:
Not established
Terminal Length:
0.688 inches
Body Length:
0.360 inches
Body Width:
0.385 inches
Body Height:
0.170 inches
Center To Center Distance Between Terminals Parallel To Length:
0.200 inches
Terminal Diameter:
0.025 inches
Schematic Diagram Designator:
No common or grounded electrode (s)
Anode Type:
Solid
Electrical Polarization:
Polarized
Polarized Features Provided:
Features Provided:
Features Provided: Hermetically sealed case
Features Provided: Hermetically sealed case Capacitance Value Per Section:
Features Provided: Hermetically sealed case Capacitance Value Per Section: 0.470 microfarads single section
Features Provided: Hermetically sealed case Capacitance Value Per Section: 0.470 microfarads single section Nonderated Operating Temp:
Features Provided: Hermetically sealed case Capacitance Value Per Section: 0.470 microfarads single section Nonderated Operating Temp: Between -80.0 degrees celsius and 85.0 degrees celsius
Features Provided: Hermetically sealed case Capacitance Value Per Section: 0.470 microfarads single section Nonderated Operating Temp: Between -80.0 degrees celsius and 85.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section:
Features Provided: Hermetically sealed case Capacitance Value Per Section: 0.470 microfarads single section Nonderated Operating Temp: Between -80.0 degrees celsius and 85.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 50.0 dc single section
Features Provided: Hermetically sealed case Capacitance Value Per Section: 0.470 microfarads single section Nonderated Operating Temp: Between -80.0 degrees celsius and 85.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 50.0 dc single section Tolerance Range Per Section:
Features Provided: Hermetically sealed case Capacitance Value Per Section: 0.470 microfarads single section Nonderated Operating Temp: Between -80.0 degrees celsius and 85.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 50.0 dc single section Tolerance Range Per Section: -10.00/+10.00 percent single section
Features Provided: Hermetically sealed case Capacitance Value Per Section: 0.470 microfarads single section Nonderated Operating Temp: Between -80.0 degrees celsius and 85.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 50.0 dc single section Tolerance Range Per Section: -10.00/+10.00 percent single section Case Material:
Features Provided: Hermetically sealed case Capacitance Value Per Section: 0.470 microfarads single section Nonderated Operating Temp: Between -80.0 degrees celsius and 85.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 50.0 dc single section Tolerance Range Per Section: -10.00/+10.00 percent single section Case Material: Metal
Features Provided: Hermetically sealed case Capacitance Value Per Section: 0.470 microfarads single section Nonderated Operating Temp: Between -80.0 degrees celsius and 85.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 50.0 dc single section Tolerance Range Per Section: -10.00/+10.00 percent single section Case Material: Metal Capacitive Electrode Material:
Features Provided: Hermetically sealed case Capacitance Value Per Section: 0.470 microfarads single section Nonderated Operating Temp: Between -80.0 degrees celsius and 85.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 50.0 dc single section Tolerance Range Per Section: -10.00/+10.00 percent single section Case Material: Metal Capacitive Electrode Material: Tantalum
Features Provided: Hermetically sealed case Capacitance Value Per Section: 0.470 microfarads single section Nonderated Operating Temp: Between -80.0 degrees celsius and 85.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 50.0 dc single section Tolerance Range Per Section: -10.00/+10.00 percent single section Case Material: Metal Capacitive Electrode Material: Tantalum Dissipation Factor At Reference Tempurature In Percent:

Solder

Terminal Surface Treatment:

NSN 5910-01-014-6443

Electrolytic Fixed Capacitor - Page 2 of 2



Terminal Type	And	Quantity:
---------------	-----	-----------

2 uninsulated wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A010b0