NSN 5910-01-014-6445



Electrolytic Fixed Capacitor - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5910-01-014-6445 **Body Style:** W/o mtg facilities, terminal (s) on one end Reliability Indicator: Not established **Terminal Length:** 0.390 inches **Body Diameter:** 0.236 inches **Body Length:** 0.400 inches **Center To Center Distance Between Terminals Parallel To Diameter:** 0.125 inches **Terminal Diameter:** 0.020 inches **Schematic Diagram Designator:** No common or grounded electrode (s) **Anode Type:** Solid **Impedance At Minimum Operating Tempurature In Ohms:** 6.2 **Electrical Polarization:** Polarized **Capacitance Value Per Section:** 3.300 microfarads single section **Nonderated Operating Temp:** Between -55.0 degrees celsius and 85.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 50.0 dc single section **Tolerance Range Per Section:** -10.00/+10.00 percent single section Case Material: **Plastic Capacitive Electrode Material: Tantalum Dissipation Factor At Reference Tempurature In Percent:** 6.000 Dc Leakage At Reference Temp: 5.000 microamperes **Terminal Surface Treatment:** Solder

Terminal Type And Quantity:

2 uninsulated wire lead

NSN 5910-01-014-6445

Electrolytic Fixed Capacitor - Page 2 of 2



C	ha	Ιf	1	ife	
•	ııe		_	.II C	

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A010b0