

View Online at <https://aerobasegroup.com/nsn/5910-01-015-1685>

**Body Style:**

W/thd mtg bushing, terminals on opposite ends/w/thd mtg bushing, terminals on opposite ends/w/thd mtg bushing, terminals on opposite ends

**Reliability Indicator:**

Not established/not established/not established

**Width Across Flats:**

Between 0.241 inches and 0.241 inches and 0.241 inches and 0.250 inches 0.250 inches 0.250 inches

**Terminal Length:**

0.500 inches 0.500 inches 0.500 inches

**Body Length:**

0.499 inches

**Continuous Current Rating In Amps:**

10.0

**Terminal Diameter:**

0.040 inches

**Schematic Diagram Designator:**

Feedthrough

**Mounting Facility Screw Thread Series Designator:**

Unf

**Mounting Facility Type And Quantity:**

1 threaded bushing

**Capacitance Value Per Section:**

1.000 microfarads single section

**Voltage Temperature Limits Per Section In Percent Capacitance Change:**

-5.0/+5.0 without voltage applied single section

**Nonderated Operating Temp:**

Between -55.0 degrees celsius and 125.0 degrees celsius

**Thread Size:**

0.190 inches

**Nonderated Continuous Voltage Rating And Type Per Section:**

50.0 dc single section

**Tolerance Range Per Section:**

-20.00/+20.00 percent single section

**Case Material:**

Metal

**Insulation Resistance At Reference Temp:**

700.0 megohms

**Dissipation Factor At Reference Temperature In Percent:**

4.0000

**Terminal Surface Treatment:**

Solder

**Terminal Type And Quantity:**

2 uninsulated wire lead

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A010b0