## NSN 5910-01-015-3041



Electrolytic Fixed Capacitor - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5910-01-015-3041 **Body Style:** W/o mtg facilities, axial terminals **Reliability Indicator:** Not established **Terminal Length:** 2.500 inches **Body Diameter:** 1.000 inches **Body Length:** 1.031 inches **Terminal Diameter:** 0.040 inches **Schematic Diagram Designator:** No common or grounded electrode (s) **Anode Type:** Etched foil **Electrical Polarization:** Polarized **Capacitance Value Per Section:** 270.000 microfarads single section **Nonderated Operating Temp:** Between -55.0 degrees celsius and 105.0 degrees celsius Dc Leakage At Maximum Operating Temp: 720.0 microamperes Nonderated Continuous Voltage Rating And Type Per Section: 250.0 dc single section **Tolerance Range Per Section:** -0.00/+255.00 microfarads single section Case Material: Metal **Capacitive Electrode Material:** Aluminum Dc Leakage At Reference Temp: 120.000 microamperes **Terminal Surface Treatment:** Copper **Terminal Type And Quantity:** 2 uninsulated wire lead Shelf Life: N/a

**Unit Of Measure:** 

## NSN 5910-01-015-3041

Electrolytic Fixed Capacitor - Page 2 of 2



| _  |     |         |     |   |  |
|----|-----|---------|-----|---|--|
| 11 | em) | <br>tor | 172 | n |  |
|    |     |         |     |   |  |

No

Fiig:

A010b0