Paper-plastic Dielectric Metallized Fixed Capacitor - Page 1 of 1



NSN 5910-01-015-3946 View Online at https://aerobasegroup.com/nsn/5910-01-015-3946 **Body Style:** W/o mtg facilities terminal (s) on one surface **Reliability Indicator:** Not established **Terminal Length:** 1.000 inches **Body Length:** Between 0.810 inches and 0.830 inches **Body Width:** Between 0.410 inches and 0.430 inches **Body Height:** Between 0.290 inches and 0.310 inches Center To Center Distance Between Terminals Parallel To Length: Between 0.740 inches and 0.760 inches

Terminal Diameter:

Between 0.024 inches and 0.028 inches

Schematic Diagram Designator:

No common or grounded electrode (s)

Capacitance Value Per Section:

0.100 microfarads single section

Nonderated Operating Temp:

Between -55.0 degrees celsius and 105.0 degrees celsius

Nonderated Continuous Voltage Rating And Type Per Section:

400.0 dc single section

Tolerance Range Per Section:

-10.00/+10.00 percent single section

Case Material:

Plastic

Insulation Resistance At Reference Temp:

100000.0 megohms

Dissipation Factor At Reference Tempurature In Percent:

Terminal Type And Quantity:

2 uninsulated wire lead

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A010b0