## NSN 5910-01-015-8166

**Body Style:** 

**Dielectric Material:** 

**Test Data Document:** 

Paper and plastic polyethylene terephthalate

Plastic Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-015-8166

W/o mtg facilities, terminal (s) on one surface **Reliability Indicator:** Not established **Body Length:** 4.562 inches **Body Width:** 3.750 inches **Body Height:** 4.750 inches **Center To Center Distance Between Terminals Parallel To Length:** 2.000 inches **Terminal Diameter:** 0.216 inches **Terminal Height From Body:** 1.375 inches **Schematic Diagram Designator:** No common or grounded electrode (s) **Internal Electrical Connection Type:** Extended foil **Features Provided:** Hermetically sealed case **Insulation Resistance At Maximum Operating Temp:** 15.0 megohm-microfarads **Capacitance Value Per Section:** 15.000 microfarads single section **Nonderated Operating Temp:** Between -55.0 degrees celsius and 85.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 1500.0 dc single section **Tolerance Range Per Section:** -10.00/+10.00 percent single section **Case Material:** Metal **Insulation Resistance At Reference Temp:** 1500.0 megohm-microfarads **Dissipation Factor At Reference Tempurature In Percent:** 1.0000

81349-mil-c-19978 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

## NSN 5910-01-015-8166

Plastic Dielectric Fixed Capacitor - Page 2 of 2



Terminal Type And Quantity:
2 standoff, threaded stud
Specification Data:
81349-mil-c-19978/3d government specification
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A010b0