

View Online at <https://aerobasegroup.com/nsn/5910-01-016-1787>

Thread Class:

2a

Body Style:

Cylindrical

Overall Length:

0.540 inches

Terminal Length:

0.080 inches

Bushing Diameter:

0.120 inches

Bushing Length:

0.156 inches

Overall Diameter:

0.160 inches

Temperature Coefficient Of Capacitance In Ppm Per Deg Celsius:

0.0 single section

Tolerance Of Temperature Coefficient In Ppm Per Deg Celsius:

-15.0/+15.0 single section

Terminal Diameter:

0.040 inches

Quality Factor At 25 Deg Celsius:

10000.0

Mounting Facility Screw Thread Series Designator:

Uns

Inclosure Type:

Encased

Terminal Location:

Adjustment control end bent forward

Tuning Characteristic:

Straight line capacity single section

Adjustment Device Torque:

Between 0.500 inch-ounces and 5.000 inch-ounces

Bushing Shape:

Round

Mounting Facility Type And Quantity:

1 threaded bushing

Thready Qty Per Inch (tpi):

80

Nonderated Operating Temp:

Between -55.0 degrees celsius and 125.0 degrees celsius

Thread Size:

0.120 inches

Capacitance Range In Picofarads:

+0.35/+3.50 single section

Nonderated Voltage Rating And Type:

250.0 dc continuous single section

Adjustment Device Drive Type And Quantity:

1 slotted screw

Capacitance Drift In Picofarads:

0.01 single section

Terminal Type And Quantity:

1 turret

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A096a0