

View Online at <https://aerobasegroup.com/nsn/5910-01-016-9233>

Body Style:

W/o mtg facilities, axial terminals

Reliability Indicator:

Not established

Terminal Length:

2.500 inches

Body Diameter:

0.883 inches

Body Length:

2.828 inches

Terminal Diameter:

0.040 inches

Schematic Diagram Designator:

Electrod (s) grounded to case, w/gnd terminal

Impedance At Minimum Operating Tempurature In Ohms:

8.1

Electrical Polarization:

Polarized

Capacitance Value Per Section:

330.000 microfarads single section

Nonderated Operating Temp:

Between -55.0 degrees celsius and 85.0 degrees celsius

Dc Leakage At Maximum Operating Temp:

483.0 microamperes

Nonderated Continuous Voltage Rating And Type Per Section:

75.0 dc single section

Tolerance Range Per Section:

-10.00/+30.00 percent single section

Case Material:

Metal

Capacitive Electrode Material:

Aluminum

Dissipation Factor At Reference Tempurature In Percent:

10.0000

Dc Leakage At Reference Temp:

80.000 microamperes

Terminal Surface Treatment:

Solder

Case Insulation Material:

Plastic

Test Data Document:

81349-mil-c-39018 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

2 uninsulated wire lead

Specification Data:

81349-mil-c-0039018/3c government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A010b0