Electrolytic Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-017-2121

## **Body Style:**

W/o mtg facilities, axial terminals

## **Reliability Indicator:**

Established

# **Terminal Length:**

1.500 inches

## **Body Diameter:**

Between 0.120 inches and 0.151 inches

### **Body Length:**

0.286 inches

## **Terminal Diameter:**

0.020 inches

### Schematic Diagram Designator:

Electrod (s) grounded to case, w/gnd terminal

## **Electrical Polarization:**

Polarized

### **Features Provided:**

Hermetically sealed case

# **Capacitance Value Per Section:**

0.010 microfarads single section

## Nonderated Operating Temp:

Between -55.0 degrees celsius and 125.0 degrees celsius

## Nonderated Continuous Voltage Rating And Type Per Section:

50.0 dc single section

### **Tolerance Range Per Section:**

-20.00/+20.00 percent single section

### **Case Material:**

Metal

**Capacitive Electrode Material:** 

Tantalum

### **Dissipation Factor At Reference Tempurature In Percent:**

2.0000

# Dc Leakage At Reference Temp:

0.300 microamperes

# **Case Insulation Material:**

Plastic

# **Test Data Document:**

81349-mil-c-39003/1 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

# **Terminal Type And Quantity:**

2 uninsulated wire lead

Shelf Life:

N/a

Electrolytic Fixed Capacitor - Page 2 of 2



Unit Of Measure:

---

Demilitarization:

No

Fiig:

A010b0